

FIRE DETECTION UNIT (FDU)

**FOR THREE PHASE LOCOMOTIVES
(WAG9, WAG9H / WAP7 / WAP5)**

USER MANUAL

RELEASE 1.0

MAY - 2022



Submitted By



Advanced Rail Controls Private Limited

#59/1-2, G-Block, Sahakaranagar
Bangalore-560 092

INDEX

No.	Contents	Page No.
1.0	Introduction	3
2.0	Functional details	3-7
3.0	Contact details	7-8

IMPORTANT NOTICE


This is a sophisticated microcontroller-based equipment and can be serviced only by trained skilled personnel. Opening the equipment by any unauthorized person will make the warranty null and void.

1. Introduction

The Fire Detection Unit, hereinafter referred as FDU, is used in the 3-phase locomotives of classes WAP5, WAP7 & WAG9 (and variants) operated in Indian Railways. The FDU works by sensing the presence of smoke particles in a sample of the machine room air. In case of presence of smoke (or fire) it generates an alarm by activating a relay, which is used in the locomotive control circuit to annunciate to the driver and also to cut off the locomotive power. Two levels of alarms are generated.

2. Functional Details


2.1 System Architecture



The working principle of the FDU is explained in the block diagram. A non-metallic pipe is laid along the machine room wall, which contains small holes at predefined intervals and pre-defined size. One end of the pipe is connected to the FDU through a PG29 coupler joint. The Fig-1 given below illustrates this arrangement.

Due to the suction fan in the FDU, machine room air will be sucked into the pipe through the small holes distributed along the length of the pipe. Due to the small diameter holes, only a representative sample of the machine room air will enter the FDU. The air sample collected inside the FDU chamber comes in contact with the smoke sensor. There are two smoke sensors. The smoke sensor works

according to the principle of scattered light by smoke particles, as defined in the specification. If the air contains smoke particles beyond the pre-defined threshold, the sensor activates. The smoke sensor outputs are connected to a microcontroller (ARM microcontroller) for activating the alarms, displays and output relays.




The condition of the sampled air is continuously monitored using an air monitoring system. A sample of the air is passed through an air filter and the flow is monitored. In case the air contains dust particles beyond the acceptable levels, it could affect the performance of the FDU and also may lead to false alarm. If the dust content is more than acceptable, the air flow measuring system will generate alarm to enable cleaning of the FDU.

The front panel is provided with a cluster of LEDs as defined in the specification. The LEDs are intended to give status of equipment in operation (Green), Fault/malfunction (Yellow) and Smoke Alarm 1 & Smoke Alarm 2 (Red). Also in our design we have eliminated Potentiometer and banana sockets which is used to set calibration voltage for Air flow sensor and to measure voltage in the multimeter respectively, in our design we have provided Membrane Up and down keys to set calibration voltage and graphical display to display the calibration voltage instead of using multimeters. The panel has also a reset button.


2.2 Connection diagram


The alarm status of the FDU is made available through potential free relay contacts (5 relays) wired as given in Fig-2. These relay contacts are wired to the loco electronics (VCU) for providing visual indication to the driver as well as for fault log and activation of traction circuit.




2.3 Initial Power ON setup

After power ON the start-up screen appears. The display shows airflow voltage and the Operation LED (Green) will glow. Initially the FDU has to be calibrated.






To calibrate press either **Up/Down** button now another screen appears “**To calibrate press (Ⓢ) button**”. Then it shows “**Calibrating.....**”. When calibration is completed, final screen appears “**Calibrated voltage = +/-0.05V**”.



Connect the suction pipe to the FDU. When all the holes of the pipe are closed Fault/Malfunction LED (Yellow) will glow.



If any smoke is detected at any suction point of the pipe either Alarm smoke detector 1 or Alarm smoke detector 2 (Red) will glow.



If the FDU detects any fault/malfunction or any smoke is detected then it has to be calibrated once again.

3.0 CONTACT DETAILS

For any warranty/service-related queries, please contact

Bangalore HQ: Royapuram / Erode / Kalyan / Vadodara sheds

Mr. Manjunath. Naik,
 Head, Service Department,
 Advanced Rail Controls Private Limited,
 # 59/1&2, Above Bank of India,
 G-Block, Sahakara Nagar
 Bangalore-560 092
 Phone: +91 80 42401212, +91 80 42401226
 Fax: +91 80 42401213
 Cell: + 91 9886610263
 E-Mail: <mail@arc.net.in>, <manjunath@arc.net.in>
 URL: <www.arc.net.in>

Lalaguda / Vishakhapatnam / Kazipet / Vijayawada

Chaitanya. S [Base Station: Lalaguda]
 Cell: + 91 7989759891
 Chaitanya. M [Base Station: Kazipet]
 Cell: + 91 7989247708

CLW / Dankuni

Rahul Deo Sharma [Base Station: Chittaranjan]
Cell: + 91 9334804107

Piyush Prasad [Base Station: Chittaranjan]
Cell: + 91 9386203249

Ajni / Itarsi / Bhusawal / Bhopal / New Katni

Pankaj Ramesh Rao Hedau [Base Station: Nagpur]
Cell: + 91 9021090829

Ghaziabad / Tuglakabad / RDSO

Subhash [Base Station: New Delhi]
Cell: + 91 9212846380

Pappu Kumar Shah [Base Station: Ghaziabad]
Cell: + 91 8051402441

Tatanagar / Bandamunda

Vivek Kumar Mukhi [Base Station: Tatanagar]
Cell: + 91 7762905971

Deepak Kumar [Base Station: Bandamunda]
Cell: + 91 8144914896

Gomoh / Howrah / Kancharapara

Ravikumar Vishwakarma [Base Station: Gomoh]
Cell: + 91 7050029319

Anchal [Base Station: Kancharapara]
Cell: + 91 8092793337